AM SUCTION RANGE

DATA SHEET 35



SAM suction units are designed to run quietly for long periods of time. At their heart is a state of the art oil-free diaphragm pump combined with multiple safety features including internal filters (hydrophobic) and overflow control valves.

A range of accessories is available including bedside stands, foot switch controls, disposable tubing and curettes, stainless steel cannulae and obstetric suction cups.





SAM

OPERATING THEATRE UNIT

Vacuum 0 to 0.9 bar / 0 to 675 mmHg

Flow rate 50 l/min

Collection Jars 2 x 2 litre or 2 x 4 litre

Unit Dimensions 84 x 39 x 33 (H x W x D cm)2x2

84 x 43 x 33 (H x W x D cm)2x4

Weight **Noise Level** 55dB

Voltage 230v +/- 10%~ 50/60Hz

110v +/- 5%~ 50/60Hz

Complies with Medical Directive 93/42/EEC

BS FN ISO 10079-1 BS EN 60601-1 BS EN 60601-1-2









The SAM 35 aspirator is a top quality surgical suction unit providing high flow, high vacuum performance. The unit is designed primarily for major operating theatre use and can also be used in lipo-suction procedures. Its reputation for reliability and ease of operation has established it among the most widely used units in the medical world today.

As standard, the SAM 35 incorporates two autoclaveable SAM 2 collection vessels fitted with float valve systems, providing automatic shut-off to avoid over-flow. Similarly, the SAM 35 can be provided with two 4-litre SAM 4 autoclaveable jars on request.. The SAM 35 is also available with a choice of disposable collection systems including Serres, Abbott, VacSax and Pennine. Other disposable collection systems can also be fitted to the SAM 35 on request.

